Single Phase Meter Bases

	200 AMP OH	200 AMP UG	320 AMP OH/UG	200 AMP COMBO W/LOAD CENTER	125/200 AMP MULTI- METER SOCKETS
Milbank	U7021-DL-TG	U1980-O	U1797-O-K3L-K2L-BL	U5168-XTL-200** U5891-X-2/200**	U125x-X-Kx Series**
Durham		1006240A*			
Eaton		UTRS223ACH			1MPxxxxRRL Series**
Square D					MPRxxxxx Series**

**Using to gain experience, prior TCEMC approval required.

Three Phase Self Contained Meter Bases

	200 AMP OH/UG	320 AMP OH/UG
Milbank	U9701-RRL-BL	U2594-X-K7-K6
Durham	UT-H7213B	UT-H7330U
Siemens	40407-0250	44707-02

Requirements

- 1. UL Approved with label (Underwriters Laboratories)
- 2. Ringless steel construction (galvanized and painted gray)
- 3. All Network, Multi Position, and Gang bases must have pre approval from Engineering Department.
- 4. Barrel lock provisions are optional.
- 5. Non approved meter bases will not be energized by TCEMC.
- 6. All UG bases require 3" knockout & slip coupling
- 7. Line side meter base lugs (including necessary hex nuts) are required for TCEMC to make the electrical service connection.